




ロングアイボルトB型

S307




※ナット・ワッシャー各1個付

品番	D	L	H	B	捻径	重量(g)	使用荷重(kg)
LBB-6 X40	5	16	31	40	M-6	27	50
X60	5	16	31	60	M-6	29	50
X80	5	16	31	80	M-6	32	50
X100	5	16	31	100	M-6	37	50
LBB-8 X60	7	19	39	60	M-8	58	80
X80	7	19	39	80	M-8	62	80
X100	7	19	39	100	M-8	65	80
X120	7	19	39	120	M-8	75	80
LBB-10X80	8	25	50	80	M-10	110	150
X100	8	25	50	100	M-10	120	150
X120	8	25	50	120	M-10	130	150
X140	8	25	50	140	M-10	140	150
LBB-12X100	10	29	59	100	M-12	195	220
X120	10	29	59	120	M-12	210	220
X140	10	29	59	140	M-12	235	220

※上記以外のサイズもご照会下さい。

つばなしロングアイボルト S3191




※ナット・ワッシャー各2個付

品番	D	L	H	B	T	捻径	質量(g)	使用荷重(kg)
LCC-6×60	5	16	30	60	58	M-6	24	50
LCC-8×60	7	18	36	60	55	M-8	44	80
LCC-10×80	8	24	44	80	75	M-10	92	150
LCC-12×100	10.5	28	55	100	87	M-12	160	220
LCC-16×145	14.5	38	70	145	127	M-16	440	450
LCC-6L×120	5	16	30	120	75	M-6	36	50
LCC-8L×120	7	18	36	120	80	M-8	61	80
LCC-10L×160	8	24	44	160	105	M-10	129	150
LCC-12L×200	10.5	28	55	200	130	M-12	240	220

※上記以外のサイズもご照会下さい。


リングキャッチ (レギュラータイプ) S7350

別名 連結環とも呼ばれます。



品番	D	S	L	B1	B2	E	重量(g)	使用荷重(kg)
SH-2.5	2.5	4.5	25	9	7.5	3	3	20
SH-3	3	5	29	10	8.5	3.3	6	30
SH-4	4	6	35	11	9.5	4.4	11	50
SH-5	5	7	42	13	11.5	5.4	20	80
SH-6	6	8	49	14	12	6.5	33	150
SH-8	8	11	61	17	15	8.5	73	350
SH-9	9	12	67	20	18	9.5	101	500
SH-10	10	13	69	22	20	10.5	138	700
SH-12	12	14	80	26	23	14	230	800

鉄ユニクロリングキャッチ W7350



品番	D	S	L	B1	B2	E	重量(g)	使用荷重(kg)
SHW-3	3.5	5	29	10	8.5	5	6	30
SHW-4	4	6	33	11	9.5	6	11	40
SHW-5	5	7	39	13	11.5	7	20	70
SHW-6	6	8	49	14	12	8	33	120
SHW-7	7	9	54	17	14	10	56	150
SHW-8	8	10	58	17	14	10.5	73	250
SHW-9	9	12	63	17.5	15	12	101	280
SHW-10	10	13	69	22	20	13	138	350
SHW-12	12	14	80	23	20	15	160	400